


BATTENS

A range of standard T8 single and twin battens .

Key Features:

- Control gear is switch start or high frequency.
- Prismatic diffuser (P) option.
- Integral HF electronic ballast options (H).
- Integral Emergency 3 hour maintained (E) option.
- Wire Guard (W), Dimmable (R), and Trough Reflector (TR) options.
- Other reflector types are available on request.
- Supplied without tubes.



Product	Length	Depth	Width
1200 Single	1230 mm	78 mm	50 mm
1500 Single	1530 mm	78 mm	50 mm
1200 Twin	1230 mm	78 mm	110 mm
1500 Twin	1530 mm	78 mm	110 mm

Diffusers	Width	Depth
Single	80 mm	70 mm
Twin	155 mm	70 mm

PRODUCT CODES

Product Code	Product	Lamp	Option Suffixes
100-005	1200 Single	1x36W	H, E, R, P
100-009	1500 Single	1x58W	H, E, R, P, W, TR
100-007	1200 Twin	2x36W	H, P
100-011	1500 Twin	2x58W	H, E, R, P, W, TR

The *NorLight* Range

Andolite Limited

Unit 21 Hopkinson Way
West Portway Industrial Estate
Andover
Hampshire. SP10 3LF

Telephone: 01264 356445
Fax: 01264 334401
Email: sales@andolite.co.uk,
Website: www.andolite.co.uk
Website: www.norlight.co.uk

For reliability and safety, we only use brand name modules and lamps