

## RECESSED UPLIGHTERS

A robust and attractive range of recessed units with long life LEDs behind a glass lens..

### Key Features:


- IP67 Class I units have a clear tempered glass lens.
- IP65 Class I units are fitted with a clear glass lens.
- All units have a stainless steel front plate.
- All units have an aluminium body with plastic recessed housing.
- Supplied with 3-core cable.
- Lamp Colour Suffix Options:
  - White (W)
  - Red (R)
  - Blue (B)
  - Green (G)
  - Yellow (Y)



IP67 – 18 Unit LED



IP67 – 15 Unit LED



IP65 – 20 Unit LED

Product	Diameter	Depth
IP 67 Circular – 18 Unit LED	198 mm	267 mm

Product	Width	Height	Depth
IP67 Square – 15 Unit LED	105 mm	105 mm	112 mm
IP65 Square – 20 Unit LED	170 mm	170 mm	124 mm

### The *NorLight* Range

#### Andolite Limited

Unit 21 Hopkinson Way  
West Portway Industrial Estate  
Andover  
Hampshire. SP10 3LF

Telephone: 01264 356445  
Fax: 01264 334401  
Email: sales@andolite.co.uk,  
Website: www.andolite.co.uk  
Website: www.norlight.co.uk

### PRODUCT CODES

Product Code	Product	Watts	Colour Suffixes
104-420	LED Recessed Uplighter – IP67 Circular	5.0 W	W/R/B/G/Y
104-421	LED Recessed Uplighter – IP67 Square	5.0 W	W/R/B/G/Y
104-422	LED Recessed Uplighter – IP65 Square	5.0 W	W/R/B/G/Y

For reliability and safety, we only use brand name modules and lamps