

NON-CORROSIVES

A range of single and twin enclosed non-corrosive luminaires for dusty or humid environments with hook suspension.

The body is an extremely durable injection moulded, heat resistant polystyrene with an IP65 polyurethane gasket injected in to the body.

Key Features:

- Control gear is switch start or high frequency mounted on galvanised steel trays painted white.
- Standard clear acrylic diffuser, or polycarbonate (P) option.
- Integral HF electronic ballast options (H).
- 110v Option (110).
- Integral Emergency 3 hour maintained (E) option.
- T5 versions available to order.
- Dimmable versions for 18W, 36W and 58W available to order.
- Supplied without tubes.



Product	Length	Height	Width
600 Single	666 mm	125 mm	120 mm
1200 Single	1268 mm	125 mm	120 mm
1500 Single	1570 mm	125 mm	120 mm
1800 Single	1872 mm	125 mm	120 mm
600 Twin	666 mm	125 mm	180 mm
1200 Twin	1268 mm	125 mm	180 mm
1500 Twin	1570 mm	125 mm	180 mm

PRODUCT CODES

Product Code	Product	Lamp	Option Suffixes
102-001	600 Single	1x18W	H, P, 110
102-003	1200 Single	1x36W	H, E, P, 110
102-005	1500 Single	1x58W	H, E, P, 110
102-007	1800 Single	1x70W	H, E, P
102-002	600 Twin	2x18W	H, E, P, 110
102-004	1200 Twin	2x36W	H, E, P, 110
102-006	1500 Twin	2x58W	H, E, P, 110

The *NorLight* Range

Andolite Limited

Unit 21 Hopkinson Way
West Portway Industrial Estate
Andover
Hampshire. SP10 3LF

Telephone: 01264 356445
Fax: 01264 334401
Email: sales@andolite.co.uk,
Website: www.andolite.co.uk
Website: www.norlight.co.uk

For reliability and safety, we only use brand name modules and lamps