


OPTIMA

A quality polycarbonate luminaire to IP44 standard for medium or large settings. For use in mains and emergency lighting applications.

A slim black or white base with a large impact resistant diffuser, gives a low energy, long life solution for wall or ceiling mounting. Available in two sizes.

Key Features:

- A strong, practical luminaire combining both elegance and durability.
- Supplied complete with ballast and choice of energy efficient lamp.
- Impact resistant opal diffuser.
- Suitable for wall or ceiling mounting.
- Integral HF electronic ballast options (H).
- Integral Emergency 3 hour maintained (E) and non-maintained (NM) options



For Use Anywhere:

Halls, Corridors, Conference Centres, Shopping Centres, Hotels, Galleries, Churches, Function Rooms, Schools and Hospitals.

Product	Outer Diameter	Housing Depth
Optima 245	245 mm	125 mm
Optima 340	340 mm	115 mm

PRODUCT CODES

Product Code	Diameter	Lamp	Base Colour	Option Suffixes
107-025	245 mm	GLS	White	
107-026	245 mm	16W2D	White	H or NM
107-040	340 mm	28W2D	White	H, E, HE or NM
107-045	340 mm	38W2D	White	H, E, HE or NM
107-026BL	245 mm	16W2D	Black	H or NM
107-040BL	340 mm	28W2D	Black	H, E, HE or NM
107-045BL	340 mm	38W2D	Black	H, E, HE or NM

The *NorLight* Range

Andolite Limited

Unit 21 Hopkinson Way
West Portway Industrial Estate
Andover
Hampshire. SP10 3LF

Telephone: 01264 356445

Fax: 01264 334401

Email: sales@andolite.co.uk,

Website: www.andolite.co.uk

Website: www.norlight.co.uk

For reliability and safety, we only use brand name modules and lamps